

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Information relevant to liaison statement L802.16-08/004 from ITU-R Working Party 5D on ACS values	
Date Submitted	2008-03-04	
Source(s)	Roger Marks NextWave Wireless Inc.*	E-mail: r.b.marks@ieee.org * http://standards.ieee.org/faqs/affiliationFAQ.html >
Re:		
Abstract	This contribution provides information relevant to preparation of a possible response to a liaison statement (IEEE L802.16-08/004) from ITU-R Working Party 5D on "Request for clarification on OFDMA TDD WMAN BS and MS ACS values".	
Purpose	For consideration by the ITU-R Liaison Group in its consideration of a possible response to IEEE L802.16-08/004, as a liaison statement to WP 5D or to the WiMAX Forum.	
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups.</i> It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.	

Information relevant to liaison statement L802.16-08/004 from ITU-R Working Party 5D on ACS values

Roger B. Marks

NextWave Wireless Inc.

Introduction

ITU-R WP 5D's liaison statement (D/TEMP/6(Rev.1), or IEEE L802.16-08/003), entitled "Request for clarification on OFDMA TDD WMAN BS and MS ACS values," was addressed to IEEE and the WiMAX Forum. That document concerned ACS values as computed from ACR and SNR values.

Viewing the liaison statement from an IEEE 802.16 perspective:

(i) The key issue in the liaison is a contradiction between M.1457 and M.2116. However, IEEE has not participated in and has any position regarding M.2116. Therefore, it is not responsible for any contradiction.

(ii) The calculations in the liaison statement make use of numbers in OFDMA TDD WMAN, but those numbers are not in IEEE Std 802.16.

This contribution provides relevant background information on ACR and SNR values in IEEE Std 802.16 and Recommendation ITU-R M.1457.

ACR in IEEE 802.16 and ITU-R M.1457

OFDMA TDD WMAN, in Recommendation ITU-R M.1457, uses the requirements:

- Min adjacent channel rejection at BER = 10^{-6} for 3 dB degradation C/I
 - *16-QAM-3/4 11 dB
 - *64-QAM-2/3 4 dB
- Min alternate channel rejection at BER = 10^{-6} for 3 dB degradation C/I
 - *16-QAM-3/4 30 dB
 - *64-QAM-2/3 23 dB

The recommendation quotes IEEE 802.16 subclause 8.4.13.2 as the source of these figures.

Here is the historical track in IEEE 802.16:

(1) These same numbers originated in IEEE 802.16a for WirelessMAN-OFDMA. However, IEEE 802.16a doesn't detail the conditions, including the BER.

(2) IEEE 802.16-2004 uses these same numbers as well. It still does not mention 10^{-6} BER normatively. However, it does mention it in Clause 12 (Profiles), where it says:

- First adjacent channel rejection at BER= 10^{-6} for 3 dB degradation C/I
 - *16-QAM-3/4 11 dB
 - *64-QAM-3/4 4 dB
- Second adjacent channel rejection at BER= 10^{-6} for 3 dB degradation C/I
 - *16-QAM-3/4 30 dB
 - *64-QAM-3/4 23 dB

This looks a lot like the OFDMA TDD WMAN numbers. However, it specifies 64-QAM-3/4, while the OFDMA TDD WMAN text says 64-QAM-2/3. It is not clear why there is a difference.

(3) IEEE Std 802.16e did not change any of these numbers.

(4) The current revision draft 802.16Rev2D3 is proposing to change the numbers to:

-Adjacent

*16-QAM-3/4 10 dB

*64-QAM-3/4 4 dB

-Nonadjacent

*16-QAM-3/4 29 dB

*64-QAM-3/4 23 dB

So it is proposing to change all four of the specs (the ACR in two cases and the specified coding rate in the other two).

SNR in IEEE 802.16 and ITU-R M.1457

Regarding SNR, OFDMA TDD WMAN uses the requirements as follow:

-Min SNR requirements for BER = 10^{-6} with CTC in AWGN channel (the min SNR requirements are used along with Eq. 149b to define sensitivity specifications for CTC)

*16-QAM-3/4 with 54 bytes block size 12.7 dB

*64-QAM-2/3 with 48 bytes block size 16.9 dB

*64-QAM-3/4 with 54 bytes block size 18 dB

*[other modulation/coding also specified]

The profile quotes IEEE 802.16 subclause 8.4.13.1 as the source of these figures. However, those figures do not exist in IEEE Std 802.16.

Here is the historical track in 802.16:

IEEE 802.16-2004 does not specify any minimum SNR. In 8.4.13.1, it specifies minimum receiver sensitivity, and it includes a table of “assumptions” (not minimum requirements) about the SNR.

The assumptions for the three main cases are:

*16-QAM-3/4 18.2 dB

*64-QAM-2/3 22.7 dB

*64-QAM-3/4 24.4 dB

IEEE Std 802.16e (including Corrigendum 1) revised the receiver requirements, renaming them as “requirements for enhanced handover performance.” It still has no requirements on SNR, but it adds detail explaining how the SNR assumption are used to calculate the receiver minimum sensitivity.

The “assumptions” on SNR were lowered:

*16-QAM-3/4 14 dB

*64-QAM-2/3 18 dB

*64-QAM-3/4 20 dB

The revision draft P802.16Rev2D3 is not proposing any change.

The sensitivity modifications came as a result of contribution C802.16maint-05.112r8:
<http://ieee802.org/16/maint/contrib/C80216maint-05_112r8.pdf>
which talked about addressing inconsistencies but did not address ACR.

Summary

This material may be useful to the 802.16 Working Group in drafting appropriate documents, such as liaison statements to WP 5D or the WiMAX Forum.
