

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	TTG and RTG clarifications	
Date Submitted	2005-03-15	
Source(s)	Joël Demarty SEQUANS Communications.	joel@sequans.com
	Ambroise Popper SEQUANS Communications	ambroise@sequans.com
Re:	IEEE P802.16REVd/D5-2004	
Abstract	Clarification of ambiguities on BS turnaround gaps TTG and RTG	
Purpose	Adopt changes.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

TTG and RTG clarifications

Joël Demarty, Ambroise Popper (SEQUANS Communications)

1. Introduction

In IEEE 802.16-2004, there is an ambiguity with the terms TTG and RTG, which apply only to the BS as explained by their definitions.

Some time, the terms TTG and RTG are also applied to the SS instead of the correct terms SSTTG and SSRTG.

Moreover, the definition of the TTG and RTG is somewhat ambiguous because it mixes the transmitter and receiver of the BS and of the SS although turnaround gap of the SS is fully described by SSTTG and SSRTG. Finally, the definition assumes the SS does not transmit during TTG which is incorrect because of the transmission delay.

Besides this problem, the parameter is meaningless for FDD system as underlined in section 12.2.3.1.3.1 and has no minimum/maximum/default values for TDD system in OFDM physical layer. Publishing an unused parameter could potentially create interoperability problems because the BS could publish a value which is not in sync with the actual structure of the map and the SS could rely on this parameter, making wrong assumptions on the structure of the map.

RTG and TTG should then be removed from DCD messages in OFDM phy.

This contribution amends changes made in IEEE P802.16-2004/Cor1/D1.

2. Text changes

[Modify definition of the definition 3.45 page 4 line 52 as indicated]

3.45 BS receive/transmit transition gap (RTG): A gap between the last sample of the uplink burst and the first sample of the subsequent downlink burst at the antenna port of the BS in a time division duplex (TDD) transceiver. This gap allows time for the base station (BS) to switch from receive to transmit mode ~~and SSs to switch from transmit to receive mode~~. During this gap, the BS ~~and SS are is~~ not transmitting modulated data but simply allowing the BS transmitter carrier to ramp up, and the transmit/receive (Tx/Rx) antenna switch to actuate, ~~and the SS receiver sections to activate~~. Not applicable for FDD systems.

[Modify definition of the definition 3.63 page 5 line 1]

3.63 BS transmit/receive transition gap (TTG): A gap between the last sample of the downlink burst and the first sample of the subsequent uplink burst in a time division duplex (TDD) transceiver. This gap allows time for the base station (BS) to switch from transmit to receive mode ~~and SSs to switch from receive to transmit mode~~. During this gap, the BS ~~and SS are is~~ not transmitting modulated

data but simply allowing the BS transmitter carrier to ramp down, the transmit/receive (Tx/Rx) antenna switch to actuate, and the BS receiver section to activate. Not applicable for FDD systems.

[Add the following text page 35 line 6]

8.1.3 Duplexing techniques and PHY Type parameter encodings

8.1.3.2 TDD operation

Change subclause 8.1.3.2.1 as indicated:

8.1.3.2.1 TTG

The TTG is a gap between the downlink burst and the subsequent uplink burst. This gap allows time for the BS to switch from transmit to receive mode ~~and SSs to switch from receive to transmit mode~~. During this gap, the BS ~~and SS are~~ is not transmitting modulated data but simply allowing the BS transmitter carrier to ramp down, the transmit/receive (Tx/Rx) antenna switch to actuate, and the BS receiver section to activate. After the gap, the BS receiver shall look for the first symbols of uplink burst. This gap is an integer number of PS durations and starts on a PS boundary.

Change subclause 8.1.3.2.2 as indicated:

8.1.3.2.2 RTG

The RTG is a gap between the uplink burst and the subsequent downlink burst. This gap allows time for the BS to switch from receive to transmit mode ~~and SSs to switch from transmit to receive mode~~. During this gap, the BS ~~and SS are~~ is not transmitting modulated data but simply allowing the BS transmitter carrier to ramp up, ~~and~~ and the Tx/Rx antenna switch to actuate, ~~and the SS receiver sections to activate~~. After the gap, the SS receivers shall look for the first symbols of QPSK modulated data in the downlink burst. This gap is an integer number of PS durations and starts on a PS boundary.

[Insert the following text page 41 line 57]

Change the definition of the 'Connection Identifier' field below Table 236 as indicated:

Connection Identifier (CID)

Represents the assignment of the IE to a broadcast, multicast or unicast address. If the broadcast or multicast CID is used then it is possible to concatenate unicast MAC PDUs (with different CIDs) into a single DL burst. During a broadcast or multicast DL burst it is the responsibility of the BS to ensure that any MAC PDUs sent to an HFDD SS do not overlap (in time; taking SSTTG and SSRTG into account) any UL allocations for that SS. An HFDD SS for which a DL MAP IE and UL MAP IE overlap in time shall use the UL allocation and discard DL traffic during the overlapping period.

[Insert two rows in table 346 page 130, line 10]

TTG	7	1	TTG (in PSs). <u>Used on TDD systems only.</u>	SCa, OFDM , OFDMa
RTG	8	1	RTG (in PSs). <u>Used on TDD systems only.</u>	SCa, OFDM , OFDMa