

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Corrections to CINR measurements and reports in OFDMA PHY	
Date Submitted	2005-07-10	
Source(s)	Ran Yaniv, Tal Kaitz, Danny Stopler, Yaron Alpert, Yonah Lasker	ran.yaniv@alvarion.com
	Alvarion	
	Yuval Lomnitz, Uri Perlmutter, Nir Metzger	yuval.lomnitz@intel.com
	Intel	uri.perlmutter@intel.com
	Jaehae Cho	
	Samsung Electronics	jaehae1.cho@samsung.com
	Dave Pechner	
	Arraycomm	dpechner@arraycomm.com
Re:	Call for comments, 802.16maint task group	
Abstract		
Purpose		
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Corrections to CINR measurements and reports in OFDMA PHY

Ran Yaniv, Tal Kaitz, Danny Stopler, Yaron Alpert, Yonah Lasker

Alvarion Ltd.

Yuval Lomnitz, Uri Perlmutter, Nir Metzger

Intel

1 Problem Statement

The current draft defines a CINR based mechanism for rate adaptation. This mechanism is incomplete and lacks important definitions.

1. The text does not specify to what the CINR measurement relates. Measurements on the preamble, on pilots, and even on data subcarriers of different zones, will result in different values due to varying boosting levels, cell loading, and reuse factor. Further, when adaptive beamforming is employed, CINR measurements will vary greatly depending on the allocation used for measurement.

The BS should specify the unique zone (by means of zone type and PRBS_ID in order to differentiate between multiple zones), and subset of major groups (for PUSC reuse-1 zone) on which the SS shall measure average CINR. Specifying the subset of major groups is important since different major groups may be transmitted with different power level or antenna beam (for example with 'dedicated pilot mode').

2. The text states that CINR is measured on "messages". It is not clear to which "messages" the text refers, as the SS is not required to decode or be aware of all messages in the frame. Further, the time scale of the message time indices is not defined; as a result, the averaging parameter has no meaning.
3. The text should specify that the CINR measurement should refer to non-boosted data subcarriers; hence the boost level of the preamble and pilots should be compensated for.
4. CINR estimates derived for CQICH should be kept distinct from reports triggered by REP-REQ/RSP. For example, we would want the ability to configure the CQICH to periodically report CINR on a specific zone, while triggering a one-time measurement on a different zone using REP-REQ/RSP.
5. The "physical CINR" report does not reflect the ability of the SS to successfully decode data as it does not include effects of channel selectivity, colored interference, decoder implementation and other losses. An effective SINR that represents the SS's ability to decode data should be defined.

1. An effective SINR measure must pertain to a specific target error rate, which differs between applications (low-latency voice, data with ARQ or H-ARQ, etc). Hence, the BS must specify the target error rate for which the effective SINR shall be reported.
2. The SS should be instructed to trigger a non-periodic update of effective SINR in case the CQI interval is very large, otherwise consecutive downlink transmissions will fail for the duration remaining until the next CQI report arrives at the BS. This is especially important in applications that do not employ ARQ.

The following is an outline of the proposed changes:

1. Subsection 6.3.17.4 is modified to define the operation flow for physical CINR and effective CINR reports based on periodic CQI and non-periodic REP-REQ/RSP messages.
2. The CQICH_Alloc_IE is extended to include report configuration parameters.
3. REP-REQ/RSP TLVs are added to support the different CINR measurement modes.
4. Effective CINR report should correspond to a specific target block error rate ~~prescribed reporting profile that defines the target block error rate~~ (and assumed block size) for which the best effective CINR is to be reported.
5. “Effective CINR” encoding on the 4-bit CQI channel is defined.
6. Clarifications are added to section 8.4.11.3 on CINR measurement.

2 Detailed Text Changes

6.3.2.3.43.5 CQICH Control IE

[Add the following text to page 28 line 65]

The format of CQICH Control IE is presented in Table 93. [The specific reporting value shall follow the directions indicated in the latest CQICH allocation IE \(8.4.5.4.12\).](#)

[Change the sub-clause number as follows in Page 64 line 57 and reassign new sub-clause numbers for the subsequent sub-clauses]

6.3.18-17.4 CQICH Operations DL CINR Report Operation

This section applies to OFDMA mode only. The SS transmits [either a physical CINR metric or an effective CINR metric](#) using the REP-RSP MAC message or fast-feedback (CQICH) channel.

[The physical CINR is defined in section 8.4.11.3. The effective CINR is a function of physical CINR, varying channel conditions and implementation margin. The exact measurement method used to derive the effective CINR is implementation specific. The reported effective CINR feedback shall correspond to the MCS in table 298a with which the expected block error rate, with assuming block length of 60 bytes as specified by the BS, is closest to, but does not exceed, the a target average error rate of 10% \(the target error rate may be overridden by profiles\) specified by the BS. When HARQ is employed, the computed block error rate shall only pertain to the first H-ARQ transmission. The UCD message defines multiple 'effective CINR reporting profiles', which define a target block error rate and assumed block length for that error rate.](#)

[The metric can be reported for either the preamble or a permutation zone. The manner in which the metric is derived for a permutation zone is in general implementation specific, however the BS may explicitly instruct the SS to report the metric based on measurements from data or pilots.](#)

[The SS shall implement at least one measurement scheme and negotiate its capability.](#)

6.3.18.1 DL CINR report with REP-RSP MAC message

[The REP-RSP message shall be sent by the SS in response to a REP-REQ message from the BS to report estimation of DL physical CINR or effective CINR.](#)

[REP-REQ shall indicate whether the reported metric shall apply to the preamble or to a specific permutation zone. For the report on the preamble, BS can request SS to report the CINR based on the measurement from the preamble for the different frequency reuse factors or band AMC configuration. For report on a specific permutation zone, the REP-REQ indicates the report type configuration, which includes the zone for which the CINR is to be estimated. The zone is identified by its permutation type \(PUSC with 'use all SC=0', PUSC with 'use all SC=1', FUSC, Optional FUSC, AMC AAS zone, Safety channel\), and PRBS ID. Also, the same permutation and PRBS ID can be differentiated by the STC or AAS](#)

indication. In the case of physical CINR, †The SS shall not perform a measurement in a frame in which the specified zone is not allocated, and shall retain the previous measurement. For PUSC permutation zones, the SS may be instructed to report CINR estimate for only a subset of the major groups. The SS may send a REP-RSP message in an unsolicited fashion.

In the case where the requested report configuration does not differ from the previous REP-REQ message in which CINR report was requested, the SS is required to send its response within 3 frames. A REP-REQ message shall not contain more than one TLV requesting any type of CINR report.

For the Band-AMC differential CINR reports, the effective CINR metric shall not be used.

If the BS instructs CINR reporting on an AAS zone, then the SS shall report the estimate of the physical or effective CINR measured from dedicated AAS preamble/pilot or data subcarriers that belong to slots allocated to it. For DL-PUSC in AAS mode, if major-group indication has been specified in the measurement configuration then the reported CINR shall be measured on all indicated major groups rather than on slots allocated to the SS.

[All existing text within 6.3.17.4 should go under the following title (6.3.18.2)]

6.3.18.2 Periodic CINR report with fast-feedback (CQICH) channel

[Modify the text as follows in 6.3.17.4]

~~This section describes the operation scenarios and requirements of CQICH, which is designed for H-ARQ enabled SS.~~ After an SS turns on its power, the ~~only appropriate~~ subchannels that can be allocated to the SS are all ~~kinds of~~ subchannels the SS can support except the band AMC subchannel. ~~To determine the M/C level of normal subchannels, the average CINR measurement is enough for the BS to determine the M/C levels of uplink and downlink.~~ As soon as the BS and the SS know the capabilities of both entities modulation and coding, the BS may allocate a CQICH subchannel using a CQICH IE (CQICH allocation IE or CQICH Control IE)~~a CQICH Control IE~~ for periodic CINR reports (physical CINR or effective CINR).

CQICH Allocation IE may indicate whether the reported metric shall apply to preamble or to a specific permutation zone. For the report on the preamble, BS can request SS to report the CINR based on the measurement from the preamble for the different frequency reuse factors. For the report on the specific permutation zones, the CQICH Allocation IE indicates the report type configuration, which includes the zone for which the CINR is to be estimated. The zone is identified by its permutation type (PUSC with ‘use all SC=0’, PUSC with ‘use all SC=1’, AMC AAS zone, FUSC, Optional FUSC, Safety channel), and PRBS ID. Also, the same permutation and PRBS ID can be differentiated by the STC or AAS indication. In the case of physical CINR, †The SS shall not perform a measurement in a frame in which the specified zone is not allocated, and shall retain the previous measurement. For PUSC permutation zones, the SS may be instructed to report an estimate for only a subset of the major groups. The first CQICH Allocation IE sent to the SS shall indicate the report type configuration. Only a subsequent CQICH Allocation IE may update the report type configuration for CQI channel based reports. See sections 8.4.5.4.12 and 8.4.11.3. CQICH allocated through CQICH Control IE shall use the measurement configuration defined in the

latest CQICH allocation IE. The quantization and encoding of physical CINR and effective CINR onto the Fast-Feedback channel is defined in section 8.4.5.4.10.

A effective CINR reported on the COI is interpreted as the SS's recommendation which best meets the specified target error rate for the duration remaining until the next scheduled COI report.

The SS ~~shall~~ may send an unsolicited REP-REQ message if it decides that the last effective CINR report is no longer appropriate for the duration remaining until the next periodic COI transmission. The message is used to specify the new effective CINR for the COI channel. The COI channel is identified by its CQICH_ID or by the SS's CID if the COI channel is allocated without a CQICH_ID. The SS shall not send an unsolicited update to the effective CINR of a COI channel if 'triggered update' is disabled in the CQICH Allocation IE that allocated the COI channel.

An SS may support two concurrent COI channels (not necessarily being scheduled in the same frame)-, one for ~~for~~ effective CINR reports and one for physical CINR reports, both of which refer to the same zone (or both refer to the preamble) but with a different effective CINR reporting profile. In such a case, both reported values shall be derived from the same underlying set of measurements. -The COI channel is identified by the CQICH_ID field in the CQICH Allocation IE. Support for more than one concurrent COI channel is optional and negotiated in section 11.8.3.7.X.

For the Band-AMC differential CINR reports, the effective CINR scheme shall not be used.

At any time, the BS may de-allocate the SS' CQICH by putting another CQICH **Control** IE with Duration $d = 0000$. Before the CQICH life timer which is set at the receipt of the CQICH **Control** IE expires, sending another CQICH **Control** IE overwrites all the information related to the CQICH such as Allocation Index, Period, Frame offset, and Duration. Hence, unless the BS refreshes the timer, the SS should stop reporting as soon as the timer expires. However, in case of sending the MAP IE for re-allocation or deallocation, the BS should make sure if the previous CQICH is released before it is re-allocated to another SS.

The SS sends the REP-RSP message in an unsolicited fashion to BS to trigger Band AMC operation. The triggering conditions are given by TLV encodings in UCD messages. The REP-RSP (see 11.12 for the TLV encodings) includes the CINR measurements of **five four** best bands. Only when an SS reports its BS the CINR measurements of Band AMC channels, its logical definition is differently made as follows. If the number of bands is 48 (2048 FFT in 20 MHz), the two contiguous bands are paired and renumbered the same as a 24 band system. Then, if the LSB of an SS MAC address is 1, it only uses the odd-numbered bands. If not, it only uses the even-numbered bands. Hence, for example, the LSB of an SS MAC address is 1, $(4m+2, 4m+3)$ bands are paired and the paired band is the m -th band of the SS. Similarly, for an evennumbered SS, $(4m, 4m+1)$ bands are paired and the paired band is the m -th band of the SS.

The BS acknowledges the trigger by allocating Band AMC subchannels. From the next frame when the SS sent the REPRSP, the SS starts reporting the differential of CINR **from preamble for five four** selected bands (increment: 1 and decrement: 0 with a step of 1 dB) on its CQICH. **The CQICH shall then be used for differential Band-AMC reports, regardless of the report configuration specified in the CQICH IE that allocated the current COI channel.** The CINR shall be measured as indicated in the REP-RSP message. If

the BS does not allocate the Band AMC subchannels [or send REP-REQ to indicate reporting Band AMC CINR](#) within the specified delay (CQICH Band AMC Transition Delay) in the UCD message, the SS reports the updated average CINR as indicated in the latest CQICH IE. ~~of the preamble for normal subchannel allocations~~. When the BS wants to trigger the transition to Band AMC mode or update the CINR reports, it sends the REP-REQ message (see 11.11 for the TLV encodings). When the SS receives the message, it replies with REP-RSP. When the BS receives the REP-RSP, it should synchronize the selection of bands reported and their CINR. Unless the BS allocates normal subchannels [or the CQICH IE indicates to report CINR on a zone other than Band AMC zone](#), the SS reports the differential increment compared to the most up-to-date report from the next CQI reporting frame.

[Modify table 300 (CQICH_Alloc_IE), as follows:]

Syntax	Size	Notes
...		
Duration (=d)	4 bits	A CQI feedback is transmitted on the CQI channels indexed by the (CQI Channel Index) by the SS for 2^{d-1} frames. If d is 0000, the CQICH is deallocated. If d is 1111, the SS should report until the BS command for the SS to stop.
Report configuration included	1 bit	Update to CINR report configuration is included.
If (report configuration included == 1) {		
Feedback Type	2 bits	0b00 = physical CINR feedback 0b01 = effective CINR feedback 0b10-0b11 = Reserved
Report type	1 bit	0: Report for preamble 1: Report for specific permutation zone
If (Report type == 0b0) {		Report for preamble
CINR preamble report type	1 bit	The type of preamble-based CINR report 0 – Frequency reuse factor=1 configuration. 1 – Frequency reuse factor=3 configuration.
}		
Else {		report for permutation zone
Zone permutation	3 bits	The type of zone for which to report 0b 000 – PUSC with ‘use all SC = 0’ 0b 001 – PUSC with ‘use all SC = 1’ 0b 010 – FUSC 0b 011 – Optional FUSC 0b 100 – Safety Channel region 0b 101 – AMC zone (only applicable to AAS mode) 0b 110-111 – Reserved
STC-Zone type	2 bits	0b00 – non-STC zone 0b01 – STC zone 0b10 – AAS zone 0b11 – reserved 0 – zone on which to report is not an STC zone 1 – zone on which to report is an STC zone
AAS-Zone	1 bit	0 – zone on which to report is not an AAS zone 1 – zone on which to report is an AAS zone
Zone PRBS_ID	2 bits	The PRBS_ID of the zone on which to report
If (Zone type == 0b000 or 0b001) {		
Major group indication	1 bit	If ‘0’ then the report may refer to any subchannel in the PUSC zone.
If (Major group indication == 1) {		

<u>PUSC Major group bitmap</u>	6 bits	Reported CINR shall only apply to the subchannels of PUSC major groups for which the corresponding bit is set. Bit # <i>k</i> refers to major group <i>k</i> .
}		
<u>CINR zone measurement type</u>	1 bit	0: measurement from pilot subcarriers and, if AAS zone, from AAS preamble. 1: measurement from data subcarriers
}		
<u>If (feedback type == 0b00) {</u>		<u>Physical CINR feedback</u>
<u>Averaging parameter included</u>	1 bit	
<u>If (Averaging parameter included == 1) {</u>		
<u>Averaging parameter</u>	4 bits	Averaging parameter avg used for deriving physical CINR estimates reported through COICH. This value is given in multiples of 1/16 in the range of [1/16 ... 16/16] in increasing order.
}		
}		
<u>If (feedback type == 0b01) {</u>		<u>Effective CINR feedback</u>
<u>Effective CINR reporting profile index</u>	2 bits	Index of effective CINR reporting profile, as defined in the UCD message.
<u>Triggered update enabled</u>	1 bit	0 – triggered update is disabled 1 – triggered update is enabled See section 6.2.18.2
}		
}		
...		

[Add the following text to the end of 8.4.5.4.12]

Report configuration included

Indicates whether an update to the report configuration exists in the IE. A value of '0' indicates that the SS shall use the configuration defined in the last received CQI configuration.

Report type

Indicates whether the CINR metric shall be reported on the preamble ('0') or on a permutation zone ('1').

Effective CINR reporting profile

The reporting profile to be used for determining the effective CINR to be transmitted on the CQI channel. See section 6.3.18.

Averaging parameter included

Indicate whether a new averaging parameter avg for physical CINR reports exists in the IE. A value of '0' indicates that the SS shall perform physical CINR measurements using the last known averaging parameter.

[Add new section 8.4.5.4.10.5]

8.4.5.4.10.5 Effective CINR feedback for fast-feedback channel

When the feedback type field in the CQICH_IE() is 0b01 or the effective CINR report is request by REP-REQ, the SS shall report the effective CINR, as defined in section 6.3.18, using a 4-bit encoding according to table 298a. The FEC type assumed for the MCS column is the SS's preferred FEC type, defined as the first FEC supported by both the SS and the BS (as determined during capability exchange) according to the following order:

1. CTC
2. BTC
3. ZeroTail CC
4. CC

Table 298a – Effective CINR feedback encoding

<u>Encoding</u>	<u>Effective CINR [dB]</u>	<u>MCS</u>
<u>0b0000</u>	<u>-2.8-2</u>	<u>QPSK 1/2, repetition 6</u>
<u>0b0001</u>	<u>-10</u>	<u>QPSK 1/2, repetition 4</u>
<u>0b0010</u>	<u>-1.32</u>	<u>QPSK 3/4, repetition 6</u>
<u>0b0100</u>	<u>0.54</u>	<u>QPSK 3/4, repetition 4</u>
<u>0b0101</u>	<u>26</u>	<u>QPSK 1/2, repetition 2</u>
<u>0b0110</u>	<u>3.58</u>	<u>QPSK 3/4, repetition 2</u>
<u>0b0111</u>	<u>5 10</u>	<u>QPSK 1/2</u>
<u>0b1000</u>	<u>6.5 12</u>	<u>QPSK 3/4</u>
<u>0b1001</u>	<u>11 14</u>	<u>16-QAM 1/2</u>
<u>0b1010</u>	<u>14 16</u>	<u>16-QAM 3/4</u>
<u>0b1011</u>	<u>16 18</u>	<u>64-QAM 1/2</u>
<u>0b1100</u>	<u>17.5 20</u>	<u>64-QAM 2/3</u>
<u>0b1101</u>	<u>19 22</u>	<u>64-QAM 3/4</u>
<u>0b1110</u>	<u>21 24</u>	<u>64-QAM 5/6</u>
<u>0b1111</u>	<u>---</u>	<u>A decrease in CQICH duration is recommended (effective CINR has not changed from previous CQICH slot). This encoding shall not be repeated over consecutive COI slots.</u>

[Modify the text in section 8.4.11.3 as follows]

When **physical** CINR measurements are mandated by the BS, an SS shall obtain a CINR measurement (implementation-specific). From a succession of these measurements, the SS shall derive and update estimates of the mean and/or the standard deviation of the CINR, and report them via REP-RSP messages and/or report the estimate of the mean of the physical CINR via the fast-feedback channel (CQICH).

For the REP-RSP, the following encoding shall be used unless different encoding scheme is defined. Mean and standard deviation statistics for CINR shall be reported in units of dB. To prepare such reports, statistics shall be quantized in 1 dB increments, ranging from a minimum of -10 dB (encoded 0x00) to a maximum of 53 dB (encoded 0x3F). Values outside this range shall be assigned the closest extreme value within the scale.

The method used to estimate the CINR of a single message is left to individual implementation, but the relative and absolute accuracy of a CINR measurement shall be ± 1 dB and ± 2 dB, respectively. The specified accuracy shall apply to the range of CINR values starting from 3 dB below SNR of the most robust rate, to 10 dB above the SNR of the least robust rate. See Table 336.

If physical CINR report from the preamble was instructed, then the reported CINR shall be an estimate of the CINR over the subcarriers of the preamble. For the frequency reuse configuration=3 type, the reported CINR shall be the estimate of the CINR over the modulated subcarriers of the preamble. For the frequency reuse configuration=1, the reported CINR shall be the estimate of the average CINR over all subcarriers of the preamble except the guard subcarriers and the DC subcarriers. In other words, the signal on the unmodulated subcarriers (except the guard subcarriers and the DC subcarriers) shall also be considered as noise and interference for the CINR estimate of the frequency reuse configuration=1. The reported value shall represent the average CINR on non-boosted data subcarriers of the first zone in the frame; hence preamble boosting shall be compensated for in both desired signal and interference/noise calculation.

In case physical CINR report on specific permutation zone was instructed, then the reported value shall represent the average CINR on non-boosted data subcarriers of the zone on which measurement was requested; hence pilot boosting shall be compensated for in both desired signal and interference/noise calculation.

~~If the BS instructs CINR reporting on an AAS zone, then the SS shall report the estimate of the CINR measured from dedicated AAS preamble/pilot or data subcarriers that belong to slots allocated to it. In case physical CINR reporting on STC zone is instructed, the SS shall report the average post-combined CINR. For DL-PUSC in AAS mode, if major-group indication has been specified in the measurement configuration then the reported CINR shall be measured on all indicated major groups rather than on slots allocated to the SS.~~

[Modify the following text below eq. 144]

where $r[k,n]$ received sample n within message measured at time index k in frame units; $s[k,n]$ the corresponding detected or pilot sample (with channel state weighting) ~~corresponding to received symbol~~. The message time index is incremented every frame. The SS shall maintain separate message time index counters and mean CINR estimates for REP-RSP-based reports and for Fast-Feedback-based reports. When the CINR configuration is changed

(i.e. CINR report configuration in a CQICH IE or REP-REQ message differ from the previous CQICH_IE or REP-REQ), the SS shall reset the corresponding message time index to zero.

[Modify the following text below eq. 146]

~~k is the time index for the message (with the initial message being indexed by k=0, the next message by k=1, etc.);~~

[Add the following text at the end of section 8.4.11.3]

The averaging parameter (τ_{avg}) may be sent as a DCD message TLV. Unless specified otherwise, the default averaging parameter (τ_{avg}) is $\frac{1}{4}$. When the averaging parameter (τ_{avg}) is given to an SS through REP-REQ, this value shall only be used for deriving physical CINR estimates reported through REP-RSP, and can further only be changed through another REP-REQ message. When the averaging parameter is given to a SS through CQICH_Allocation IE, this value shall only be used for deriving physical CINR estimates reported through fast-feedback channel (CQICH), and can further only be changed through another CQICH Allocation IE. An averaging parameter value sent through DCD shall not override the averaging parameter value sent in a dedicated REP-REQ message or a CQICH Allocation IE.

[Add the following section 8.4.11.4]

8.4.11.4 Optional Frequency Selectivity Characterization

In order to characterize the relationship between channel frequency selectivity and link performance in a compact form, the parameters of an effective CINR versus weighting parameter curve can be sent from the SS to the BS using an unsolicited REP-RSP TLV. When requested by the BS, the SS shall compute a quadratic approximation of an effective CINR (dB) vs. $\tau_{dB} = 10 \log(\tau)$ curve. The quadratic approximation is represented as: effective-CINR_{dB}(τ_{dB}) = $a + b \tau_{dB} + c \tau_{dB}^2$

Where a , b and c are the Y-intercept, linear, and quadratic parameters, respectively, that are to be estimated by the SS. The quadratic approximation is derived by performing a curve fit to an experimentally derived effective CINR versus τ curve.

[Add the following entry to the end of table 353, section 11.3.1]

<u>Effective CINR reporting profiles</u>	<u>ZZZ</u>	<u>4</u>	<u>Each byte corresponds to a reporting profile, starting from reporting profile #0, with the following structure: Bits #0-#2: (=n) Target block error rate, defined as $2^{-(n-2)}$. Bits #3-#7: (=k) Target block length for computing block error rate, defined as $60 * (k+1)$, in units of bytes.</u>
--	------------	----------	--

[Add the following entry to the end of table 358, section 11.4.1]

Default RSSI and CINR averaging parameter	ZZZ	1	Bit #0~3: Default averaging parameter avg for physical CINR measurements, in multiples of 1/16 (range [1/16, 16/16], 0x0 for 1/16, 0xF for 16/16). Bit #4~#7: Default averaging parameter avg for RSSI measurements, in multiples of 1/16 (range [1/16, 16/16], 0x0 for 1/16, 0xF for 16/16). The default value is 0x3.	OFDMA
---	---------------------	---	--	-----------------------

[Add the following new section]

11.8.3.7.X OFDMA SS CINR measurement capability

[Add the table as follows at pp.135, line 27]

Type	Length	Value	Scope
XXX	1	Bit #0: physical CINR measurement from the preamble Bit #1: physical CINR measurement for a permutation zone from pilot subcarriers Bit #2: physical CINR measurement for a permutation zone from data subcarriers Bit #3: Effective CINR measurement from the preamble Bit #4: Effective CINR measurement for a permutation zone from pilot subcarriers Bit #5: Effective CINR measurement for a permutation zone from data subcarriers Bit #6: Support for 2 concurrent COI channels with effective CINR reports. Bit #7: Frequency selectivity characterization report Bit #7: Reserved; shall be set to zero	SBC-REQ (see 6.3.2.3.23) SBC-RSP (see 6.3.2.3.24)

[Add the following to the 2nd table in section 11.11 (REP-REQ) of 802.16-2004 as follows]

11.11 REP-REQ management message encodings

Zone-specific physical CINR request	1.4	3	Bits #0-2: Type of zone on which CINR is to be reported 0b000: PUSC zone with 'use all SC=0' 0b001: PUSC zone with 'use all SC=1' / PUSC AAS zone 0b010: FUSC zone 0b011: Optional FUSC zone 0b100: Safety Channel region 0b101: AMC zone (only applicable to AAS mode) 0b110 - 0b111: <i>Reserved</i> Bit #3: 1 if zone for which CINR should be estimated is STC zone, 0 otherwise. Bit #4: 1 if zone for which CINR should be estimated is AAS zone, 0 otherwise. Bits #5-6: PRBS_ID of the zone for which CINR should be estimated. Ignored for Safety Channel. Bit #7: data/pilot-based CINR measurement: 0 - Report the CINR estimate from pilot subcarriers. 1 - Report the CINR estimate from data subcarriers Bits #8-13 : Reported CINR shall only be estimated for the subchannels of PUSC major groups for which the corresponding bit is set. Bit #(k+7) refers to major group k. Only applicable for CINR measurement on a PUSC zone Bits #14-17: avg in multiples of 1/16 (range is [1/16,16/16]) Bit #18: 0 – report only mean of CINR 1 – report both mean and standard deviation of CINR Bits #19-23: <i>reserved</i>
---	-----	---	---

Preamble physical CINR request	1.5	1	<p>Bits #0-1: Type of preamble physical CINR measurement 0b00 - Report the estimation of CINR measured from preamble for frequency reuse configuration=1 0b01 - Report the estimation of CINR measured from preamble for frequency reuse configuration=3 0b10 - Report the estimation of CINR measured from preamble for band AMC 0b11 - Reserved</p> <p>Bits #2-5: \bar{avg} in multiples of 1/16 (range is [1/16,16/16]) Bit #6: 0 – report only mean of CINR 1 – report both mean and standard deviation of CINR</p> <p>Bit #7: Reserved (shall be set to zero)</p>
Zone-specific effective CINR request	1.6	2	<p>Bits #0-2: Type of zone on which effective CINR is to be reported 0b000: PUSC zone with ‘use all SC=0’ 0b001: PUSC zone with ‘use all SC=1’ / PUSC AAS zone 0b010: FUSC zone 0b011: Optional FUSC zone 0b100: Reserved 0b101: AMC zone (only applicable to AAS mode) 0b110 - 0b111: Reserved</p> <p>Bit #3: 1 if zone for which effective CINR should be reported is STC zone, 0 otherwise. Bit #4: 1 if zone for which effective CINR should be estimated is AAS zone, 0 otherwise. Bits #5-6: PRBS_ID of the zone for which effective CINR should be reported. Ignored for Safety Channel. Bit #7: data/pilot-based effective CINR measurement: 0 - Report the CINR estimate from pilot subcarriers. 1 - Report the CINR estimate from data subcarriers</p> <p>Bits #8-13: Reported effective CINR shall only be estimated for the subchannels of PUSC major groups for which the corresponding bit is set. Bit #(k+7) refers to major group k. Only applicable for CINR measurement on a PUSC zone Bit #14-15: Index of effective CINR reporting profile, as defined in the UCD message. See section 6.3.18-reserved</p>
Preamble effective CINR request	1.7	1	<p>Bits #0-1: Type of preamble-based effective CINR measurement 0b00 - Report the estimation of effective CINR measured from preamble for frequency reuse configuration=1 0b01 - Report the estimation of effective CINR measured from preamble for frequency reuse configuration=3 0b10-11 - Reserved</p> <p>Bit #2-3: Index of effective CINR reporting profile, as defined in the UCD message. See section 6.3.18. Bit #4-7: Reserved (shall be set to zero)</p>
Channel selectivity report	1.8	1	<p>Bit #0: if 1 – include frequency selectivity report Bit #1-#7: reserved</p>

[Add the following tables at the end of 11.12]

REP-REQ Zone-specific physical CINR request	Name	Type	Length	Value

<p><u>Bits #0-2 = 0b000</u></p>	<p><u>PUSC zone with 'use all SC=0'</u></p>	<p><u>3.1</u></p>	<p><u>1 / 2</u></p>	<p><u>Bit #0-4: mean of physical CINR estimate for PUSC zone with 'use all SC=0' and PRBS_ID indicated in 'zone-specific physical CINR request'.</u> <u>Bit #5: Report type: 0 - CINR estimated from pilot subcarriers, 1- CINR estimated from data subcarriers</u> <u>Bit #6-7: reserved</u> <u>Bit #8-12: standard deviation of CINR estimate for PUSC zone with 'use all SC=0' and PRBS_ID indicated in 'zone-specific CINR request'.</u> <u>Bit #13-15: reserved</u></p> <p><u>Note: The 2nd byte shall only be sent if length=2.</u></p>
<p><u>Bits #0-2 = 0b001</u></p>	<p><u>PUSC zone with 'use all SC=1'</u></p>	<p><u>3.2</u></p>	<p><u>1 / 2</u></p>	<p><u>Bit #0-4: mean of physical CINR estimate for PUSC zone with 'use all SC=1' and PRBS_ID indicated in 'zone-specific physical CINR request'. CINR reported corresponds to a subset of major groups as specified in 'CINR type request'.</u> <u>Bit #5: Report type: 0 - CINR estimated from pilot subcarriers, 1- CINR estimated from data subcarriers</u> <u>Bit #6-7: reserved</u> <u>Bit #8-12: standard deviation of CINR estimate for PUSC zone with 'use all SC=1' and PRBS_ID indicated in 'zone-specific CINR request'. CINR reported corresponds to a subset of major groups as specified in 'CINR type request'.</u> <u>Bit #13-15: reserved</u></p> <p><u>Note: The 2nd byte shall only be sent if length=2.</u></p>
<p><u>Bits #0-2 = 0b010</u></p>	<p><u>FUSC zone</u></p>	<p><u>3.3</u></p>	<p><u>1 / 2</u></p>	<p><u>Bit #0-4: mean of physical CINR estimate for FUSC zone with PRBS_ID indicated in 'zone-specific physical CINR request'.</u> <u>Bit #5: Report type: 0 - CINR estimated from pilot subcarriers, 1- CINR estimated from data subcarriers</u> <u>Bit #6-7: reserved</u> <u>Bit #8-12: standard deviation of CINR estimate for FUSC zone with PRBS_ID indicated in 'zone-specific CINR request'.</u> <u>Bit #13-15: reserved</u></p> <p><u>Note: The 2nd byte shall only be sent if length=2.</u></p>

Bits #0-2 = 0b011	Optional FUSC zone	3.4	1 / 2	<p>Bit #0~4: mean of physical CINR estimate for Optional FUSC with PRBS_ID indicated in 'zone-specific physical CINR request'.</p> <p>Bit #5: Report type: 0 - CINR estimated from pilot subcarriers, 1- CINR estimated from data subcarriers</p> <p>Bit #6-7: reserved</p> <p>Bit #8~12: standard deviation of CINR estimate for Optional FUSC with PRBS_ID indicated in 'zone-specific CINR request'.</p> <p>Bit #13-15: reserved</p> <p>Note: The 2nd byte shall only be sent if length=2.</p>
Bits #0-2 = 0b100	Safety channel	3.5	5	<p>The first 20 bits for the reported bin indices and the next 20 bits for CINR reports (5 bits for each bin).</p>
Bits #0-2 = 0b101	AMC zone	3.6	1 / 2	<p>Bit #0~4: mean of CINR estimate for AMC AAS zone.</p> <p>Bit #5: Report type: 0 - CINR estimated from pilot subcarriers, 1- CINR estimated from data subcarriers.</p> <p>Bit #6-7: reserved</p> <p>Bit #8~12: standard deviation of CINR estimate for AMC AAS zone.</p> <p>Bit #13-15: reserved</p> <p>Note: The 2nd byte shall only be sent if length=2.</p>

REP-REQ Preamble physical CINR request	Name	Type	Length	Value
Bits #0-1 = 0b00	The estimation of physical CINR measured from preamble for frequency reuse configuration=1	4.1	1 / 2	<p>Bit #0~4: The mean of physical CINR estimation measured from preamble for frequency reuse configuration=1.</p> <p>Bit #5~7: reserved.</p> <p>Bit #8~12: The standard deviation of CINR estimation measured from preamble for frequency reuse configuration=1.</p> <p>Bit #13-15: reserved</p> <p>Note: The 2nd byte shall only be sent if length=2.</p>
Bits #0-1 = 0b01	The estimation of physical CINR measured from preamble for frequency reuse configuration=3	4.2	1 / 2	<p>Bit #0~4: The mean of physical CINR estimation measured from preamble for frequency reuse configuration=3.</p> <p>Bit #5~7: reserved.</p> <p>Bit #8~12: The standard deviation of CINR estimation measured from preamble for frequency reuse configuration=3.</p> <p>Bit #13-15: reserved</p> <p>Note: The 2nd byte shall only be sent if length=2.</p>

Bits #0-1 = 0b10	The estimation of physical CINR measured from preamble for Band AMC zone.	4.3	4	The estimation of physical CINR measured from preamble for band AMC subchannel. First 12 bits for the band indicating bitmap and Next 20 bits for CINR reports (5 bits per each band).
----------------------------------	---	---------------------	---	--

REP-REQ Zone specific Effective CINR request	Name	Type	Length	Value
Bits #0-2 = 0b000	PUSC zone with 'use all SC=0'	5.1	1	Bit #0-3: Effective CINR for PUSC zone with 'use all SC=0' and PRBS_ID indicated by 'Effective CINR request'. Encoding is defined in 8.4.5.4.10.5. Bit #4: Report type: 0 – effective CINR estimated from pilot subcarriers, 1- effective CINR estimated from data subcarriers Bit #5-7: 3 least significant bits of COICH_ID
Bits #0-2 = 0b001	PUSC zone with 'use all SC=1' / PUSC AAS zone	5.2	1	Bit #0-3: Effective CINR for PUSC zone with 'use all SC=1' (or PUSC AAS zone) and PRBS_ID indicated by 'Effective CINR request'. Encoding is defined in 8.4.5.4.10.5. Bit #4: Report type: 0 – effective CINR estimated from pilot subcarriers, 1- effective CINR estimated from data subcarriers Bit #5-7: 3 least significant bits of COICH_ID
Bits #0-2 = 0b010	FUSC zone	5.3	1	Bit #0-3: Effective CINR for FUSC zone with PRBS_ID indicated by 'Effective CINR request'. Encoding is defined in 8.4.5.4.10.5. Bit #4: Report type: 0 – effective CINR estimated from pilot subcarriers, 1- effective CINR estimated from data subcarriers Bit #5-7: 3 least significant bits of COICH_ID
Bits #0-2 = 0b011	Optional FUSC zone	5.4	1	Bit #0-3: Effective CINR for Optional FUSC zone with PRBS_ID indicated by 'Effective CINR request'. Encoding is defined in 8.4.5.4.10.5. Bit #4: Report type: 0 – effective CINR estimated from pilot subcarriers, 1- effective CINR estimated from data subcarriers Bit #5-7: 3 least significant bits of COICH_ID

Bits #0-2 = 0b101	AMC AAS zone	5.5	1	Bit #0-3: Effective CINR for AMC AAS zone with PRBS_ID indicated by 'Effective CINR request'. Encoding is defined in 8.4.5.4.10.5. Bit #4: Report type: 0 – effective CINR estimated from pilot subcarriers, 1- effective CINR estimated from data subcarriers Bit #5-7: 3 least significant bits of COICH_ID
-----------------------------------	------------------------------	---------------------	-------------------	---

[Note: COICH_ID applies to triggered update \(see section 6.3.18.2\) for COI channel allocated with a COICH_ID, and shall be zero in all other cases.](#)

REP-REQ Preamble Effective-CINR request	Name	Type	Length	Value
Bits #0-1 = 0b00	The estimation of effective CINR measured from preamble for frequency reuse configuration=1	6.1	1	Bit #0~3: Effective CINR based on measurement from preamble with frequency reuse configuration=1. Encoding is defined in 8.4.5.4.10.5. Bit #4-7: 4 least significant bits of COICH_ID
Bits #0-1 = 0b01	The estimation of effective CINR measured from preamble for frequency reuse configuration=3	6.2	1	Bit #0~3: Effective CINR based on measurement from preamble with frequency reuse configuration=3. Encoding is defined in 8.4.5.4.10.5. Bit #4-7: 4 least significant bits of COICH_ID

[Note: COICH_ID applies to triggered update \(see section 6.3.18.2\) for COI channel allocated with a COICH_ID, and shall be zero in all other cases.](#)

REP-REQ Channel selectivity report	Name	Type	Length	Value
Bits #0 = 1	Frequency selectivity report	6.3	3	Bit #0~7: a Bit #8~15: b Bit #16~23: c

[Add the following text at the end of the last table in 11.2]

[For the TLVs with type 3.x and 4.x, the following 5 bit physical CINR measurement encoding shall be used:](#)

	0,	<i>CINR</i>	3dB
<i>Payload bits</i>	<i>n</i> , (<i>n</i> - 4)	<i>CINR</i>	(<i>n</i> - 3), 0 <i>n</i> - 31
	31,	<i>CINR</i>	27

