
Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Reply to Comment 118 Fix for OFDMA Initial Ranging	
Date Submitted	2005-07-15	
Source(s)	Cory Modlin, Brian Johnson Texas Instruments	Voice: 301-515-3735 bfjohnson@ti.com
Re:	IEEE P802.16-2004/Cor1/D3	
Abstract	The current proposed text describes a SS procedure to receiving RNG-RSP that will fail to work sufficiently often that the procedure needs to be fixed.	
Purpose	This is a suggested modified remedy for comment 118 to fix OFDMA initial ranging	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve (s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Reply to Comment 118 Fix for OFDMA Initial Ranging

Cory Modlin, Texas Instruments

Brian F. Johnson, Texas Instruments

1. Introduction

This contribution is a reply to comment 118 outlining issues with the proposed text and outlining an alternative remedy.

According to the current draft text (IEEE P802.16-2004/Cor1/D3) (Section 6.3.10.3.1), after receiving a RNG-RSP with status "continue," the SS shall continue ranging in the PERIODIC ranging region using codes from the INITIAL ranging domain. There are three issues with this:

1. The periodic ranging region contains a normal cyclic prefix which means the phase is not continuous between symbols and there is very little tolerance for a symbol timing offset. The initial ranging attempt is done with substantial power backoff and as a result the initial timing offset estimates may not be accurate enough.
2. Following the procedure currently outlined in IEEE P802.16-2004/Cor1/D3, this implies that in the periodic ranging region, we need to detect codes from both the periodic and initial ranging domain. This increases the complexity
3. This text is potentially inconsistent with the text in section 6.3.9.5.1, paragraph 11, page 176 which implies that the SS shall send another CDMA code at the next appropriate initial ranging opportunity.

The remedy proposed in comment 118 does not properly address the issues we have raised. Even with the symbol repeated, the cyclic prefix means that there is a discontinuity between OFDMA symbols. This means that we must be precisely aligned in time in order to receive the symbol without distortion.

We believe that the SS should continue ranging in the initial ranging region rather than in the periodic ranging region. Furthermore, so that the BS knows which SSs have already received a RNG-RSP message and to control a state machine, we propose that a specific ranging code that falls outside the initial ranging domain shall be indicated by the BS in the RNG-RSP message and used by the SS during its next ranging attempt.

2. References

IEEE 802.16-2005/Cor1/D3

3. Suggested Changes

Make the following text changes to IEEE P802.16-2004/Cor1/D3:

Change the paragraph starting on Page 53 line 20 to read as follows:

- Upon receiving a Ranging Response message with continue status, the SS shall continue the ranging process as done on the first entry except with the ranging codes randomly chosen from the Initial Ranging domain sent on the Periodic Ranging region and corrections specified in the RNG-RSP message. This ranging code shall not be within the initial ranging domain.

Page 45 line number 25 through 30 should be replaced by the following bracketed text

Change the eleventh paragraph as indicated:

For OFDMA, the SS shall send a CDMA code at a power level below $P_{TX_IR_MAX}$, measured at the antenna connector. If the SS does not receive a response, the SS shall send a new CDMA code at the next appropriate Initial Ranging transmission opportunity ~~at one step higher~~ and adjust its power level. If the SS receives a RNG-RSP message containing the parameters of the code it has transmitted and status continue, it shall consider the transmission attempt unsuccessful but implement the corrections specified in the RNG-RSP and issue ~~another~~ the CDMA code specified in the RNG-RSP message after the appropriate backoff delay. If the SS receives an UL-MAP containing a CDMA allocation IE with the parameters of the code it has transmitted, it shall consider the RNG-RSP reception successful, and proceed to send a unicast RNG-REQ on the allocated BW. More details on this procedure can be found in 6.3.10.3.

}

Page 187 line 40 insert the bracketed text {

Change table 369 as indicated:

Table 369 – OFDMA – specific RNG-RSP message encodings

Name	Type	Length	Value
Ranging code attributes	150	4 5	<u>Bits 39:32 – Used to indicate the ranging code index that the SS shall use during its next ranging transmission. Applies only when the status is “continue.” This ranging code shall fall outside of the initial ranging code domain.</u> Bits 31:22 – Used to indicate the OFDM time symbol reference that was used to transmit the ranging code. Bits 21:16 – Used to indicate the OFDMA subchannel reference that was used to transmit the ranging code. Bits 15:8 – Used to indicate the ranging code index that was sent by the SS. Bits 7:0 – The 8 least significant bits of the frame number of the OFDMA frame where the SS sent the ranging code.

}