

---

Project	<b>IEEE 802.16e Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>CID for Dedicated Pilot Zones</b>	
Date Submitted	<b>2007-02-25</b>	
Source(s)	Yongsun Hwang and Jaeyong Lee Samsung Electronics Co.	<a href="mailto:y1.hwang@samsung.com">y1.hwang@samsung.com</a> <a href="mailto:kyken.lee@samsung.com">kyken.lee@samsung.com</a>
Re:	Call for comments to Cor2/D2	
Abstract	This document describes a simple restrictive measure on CID Switch IE operation for dedicated pilot zones that can significantly reduce MS complexity and power consumption	
Purpose	Approve and adopt in Cor2	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

---

## CID for Dedicated Pilot Zones

*Yongsun Hwang and Jaeyong Lee  
Samsung Electronics Co.*

### Problem Statement

1. In dedicated pilot zones, an MS can exploit only those pilots within the bursts intended for the said MS.
2. When the use of CID is toggled off via CID Switch IE, i.e., INC\_CID = 0 in DL-MAP IE, an MS can determine the location of the bursts intended for the MS, only after all bursts are fully decoded and PDU header parsed.

These suggest that, when a burst in a dedicated pilot zone is assigned to an MS via DL-MAP IE with INC\_CID = 0 (CID off), there can exist unnecessary latency, complexity, and/or performance loss in any MS operation that use pilot information. Such operations can include various synchronization functions, automatic gain control, channel estimation, and CINR measurements.

Above potential grievance can be alleviated with a simple restriction on CID Switch IE operation. Specifically, we can require DL-MAP CID inclusion mode to be toggled on, for all DL-MAP IEs allocating bursts in dedicated pilot zones. HARQ DL-MAP IE is an exception to this restriction, since RCID is always included in this IE.

### Proposed Remedy

*Add additional text as follows:*

----- Begin -----

#### **Section 8.4.5.4.3 Space-Time Coding (STC)/DL\_Zone switch IE format**

##### **Dedicated Pilots**

The optional fields Dedicated Pilots are used to support the use of open loop precoding or closed loop transmissions in which the MS has no knowledge of the precoding/beamforming matrix. When the data allocations are precoded/beamformed, then setting the Dedicated Pilots bit to 1 means the pilot symbols are precoded/beamformed in the same way as are the corresponding data subcarriers. In this case, an MS should use only the pilots that are specific to its allocation for channel estimations. [In addition, a BS should toggle CID-Switch IE\(\) such that INC\\_CID = 1 in all non-HARQ DL-MAP IEs that allocate dedicated pilot zones.](#)

----- End -----

### References

- [1] IEEE Std 802.16 Cor1/D2 (Amendment and Corrigendum to IEEE Std 802.16 2004)