

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >
Title	<b>HARQ During Sleep-Mode and Scanning</b>
Date Submitted	2007-02-25
Source(s)	Nadav Lavi <a href="mailto:nadav.lavi@alvarion.com">nadav.lavi@alvarion.com</a> Vladimir Yanover <a href="mailto:vladimir.yanover@alvarion.com">vladimir.yanover@alvarion.com</a> Giovanni Maggi <a href="mailto:giovanni.maggi.ext@siemens.com">giovanni.maggi.ext@siemens.com</a> Henri Moelard <a href="mailto:moelard@motorola.com">moelard@motorola.com</a> Anuj Puri <a href="mailto:apuri@beceem.com">apuri@beceem.com</a> Anders Lamm <a href="mailto:anders.lamm@ericsson.com">anders.lamm@ericsson.com</a> Jonathan Segev <a href="mailto:jonathan.segev@comsystemobile.com">jonathan.segev@comsystemobile.com</a>
Re:	IEEE Std 802.16-2004/Cor2/D2
Abstract	The document contains suggestions on solving IOT issues of HARQ during sleep-mode and scanning
Purpose	Adoption of proposed changes into Std 802.16-2004/Cor2/D1
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard. "Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chiar@wirelessman.org">mailto:chiar@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.

## HARQ During Sleep-Mode and Scanning

*Nadav Lavi, Vladimir Yanover - Alvarion Ltd.*

*Giovanni Maggi – Siemens*

*Henri Moelard – Motorola*

*Anuj Puri – Beceem*

*Anders Lamm – Ericsson*

*Jonathan Segev – Comsys*

### Problem definition:

The standard defines that HARQ ACK/NACK is sent in a synchronized manner. The ACKs or NACKs are sent after a pre-defined interval after the transmission of an HARQ sub-burst. On the other hand, sleep-mode allows a method for power save by defining sleep and listen periods. The listen and sleep windows can be flexibly defined. Moreover, sleep windows' size in PSC Type I can change during sleep-mode (sleep windows are not fixed size).

As both HARQ and sleep-mode are essential features there is a need to clarify how the MS and BS act when HARQ transmissions are needed on a connection that is associated to an active PSC. Similar approach should be used in periodic scanning.

### Suggested remedy:

*In 802.16-2004/Cor2/D2, insert the following paragraph before the title of Section 6.3.17.1:*

*If a Power Saving Class containing an HARQ enabled connection is active or if there is an ongoing periodic scanning procedure, then upon traffic the BS or MS may request the deactivation of the PSC or the scanning procedure, or continue with the operation of the PSC or scanning and transmit data and ACK/NACK feedback during availability intervals (in case MS is in sleep mode) or during interleaving intervals (in case MS is performing periodic scanning). The BS shall not expect the MS to transmit ACK/NACK feedback during unavailability intervals or scan intervals even in case such allocations are scheduled.*