

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>Clarifications and Improvement in the MBS definitions and procedures in 802.16REV2</b>	
Date Submitted	<b>2008-03-20</b>	
Source(s)	Kamran Etemad, Intel Nadav Lavi, Alvarion Philip Barber, Huawei	mailto: kamran.etemad@intel.com nadav.lavi@alvarion.com pbarber@huawei.com
Re:	P802.16Rev2/D3, LB26b	
Abstract	MBS definitions and procedures in the REV2 D3 draft need adjustments and some errors need to be fixed.	
Purpose	Adoption toward REV2/D3	
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups.</i> It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < <a href="http://standards.ieee.org/guides/bylaws/sect6-7.html#6">http://standards.ieee.org/guides/bylaws/sect6-7.html#6</a> > and < <a href="http://standards.ieee.org/guides/opman/sect6.html#6.3">http://standards.ieee.org/guides/opman/sect6.html#6.3</a> >. Further information is located at < <a href="http://standards.ieee.org/board/pat/pat-material.html">http://standards.ieee.org/board/pat/pat-material.html</a> > and < <a href="http://standards.ieee.org/board/pat">http://standards.ieee.org/board/pat</a> >.	

## ***Proposed Clarifications and Improvements to MBS Definitions and Procedure in 802.16REV2***

*Kamran Etemad (Intel)*  
*Nadav Lavi (Alvarion)*  
*Phillip Barber (Huawei)*

### ***Problems with Current REV2 D3 text:***

Considering the realistic deployments and operators requirements for MBS, the MBS text in REV2D3 requires some technical corrections and clarifications as follows:

1. Multi-BS MBS should be generalized to cover semi-synchronous multi-BS multicasting.
2. Single BS MBS can be considered as special case of multi-BS MBS and its not needed
3. Text needs to be clear about the parameters which need to be the same across all BS with the same zone with macro-diversity is enabled or disabled.
4. Considering most MBS deployment involve many content channels in each MBS service, the current text more clearly specify
  - How parameters associated with multiple MBS content channels and their updates can efficiently conveyed to subscribed users at the time of service initiated and subsequent updates.
  - How to minimize signaling interaction with the network while a user in idle mode switches among content channels.
  - How to minimize signaling interaction and latency with for updating MCID's for user as they cross the MBS Zones.
  - How to allow power efficiency by selectively discarding undesired content in a multi-channel MBS burst.
5. The text also need to offer allow means of delivering MBS parameters at upper layers if supported by the network.
6. The use case and value add of LCID need to be clarified.

### ***Proposed Remedies and Text Clarifications:***

#### **6.3.2.3.52 MBS\_MAP (multicast and broadcast service map) message:**

*[Replace the first paragraph in 6.3.2.3.52 with:]*

The BS shall send an MBS\_MAP message on the Broadcast CID to specify the location and size of multi-BS MBS data bursts which are located in frames that are from 2 to 5 frames in the future from the frame containing the MBS MAP message. If present, an MBS\_MAP message shall be located at the first symbol and the first subchannel in the MBS. The MBS\_MAP message format is presented in Table 153. This message includes the MBS\_DATA\_IE, Extended\_MBS\_DATA\_IE and MBS\_DATA\_Time\_Diversity\_IE which define the access information for the MBS burst. See Tables 153, 154, 155 and 156.

*[Modify 6.3.13 as:]*

#### **6.3.13 Establishment of multicast connections**

The BS may establish a DL multicast and broadcast service by creating a multicast connection with each SS to be associated with the service. Any available traffic CID value may be used for the service (i.e., there are no dedicated

CIDs for multicast transport connections). To ensure proper multicast operation, the CID used for the service is the same for all SSs on the same channel that participate in the connection. The SSs need not be aware that the connection is a multicast connection. However, for multicast and broadcast services which utilize MBS specific features, the multicast connection shall be established using a multicast CID.

The data transmitted on the connection with the given CID shall be received and processed by the MAC of each involved SS. Thus, each multicast or broadcast SDU is transmitted only once per BS channel. Since a multicast connection is associated with a service flow, it is associated with the QoS and traffic parameters for that service flow. ARQ is not applicable to multicast connections. If a DL multicast connection is to be encrypted, each SS participating in the connection shall have an additional security association (SA), allowing that connection to be encrypted using keys that are independent of those used for other encrypted transmissions between the SSs and the BS.

*[Replace the 6.3.23 in its entirety as:]*

### **6.3.23 Multicast and broadcast service (MBS)**

Multicast and Broadcast Services provides an efficient method for concurrent transport of data common to a group of users, using a common multicast CID. MBS service is offered in the downlink only and may be coordinated and optionally synchronized among a group of BS to allow macro-diversity.

The service flows associated with MBS have certain QoS parameters and may require encryption performed using a globally defined sequence of TEKs. Since a multicast connection is associated with a service flow, it is associated with the QoS and traffic parameters for that service flow. All service flows to transmit the same MBS flows, created on any SS, shall have the same service flow management encodings for QoS parameter set (11.13.4).

Service flows to carry MBS data are instantiated on individual SS participating in the service while in Normal Operation. During such instantiation the SS learns the parameters that identify the service and associated service flows. Each BS capable of providing MBS service belongs to a certain MBS Zone, which is a set of BS where the same CID and same SA is used for transmitting the content of certain service flow(s). Each MBS Zone is identified by a unique MBS\_Zone ID.

To ensure proper multicast operation on networks of BS employing MBS, the CIDs used for common MBS content and service shall be the same for all BS within the same MBS-Zone. This allows the SS which has already registered with a service to be seamlessly synchronized with MBS transmissions within an MBS\_Zone without communicating in the UL or re-registering with other BS within that MBS-Zone. The MBS\_Zone ID's shall not be reused across any two adjacent MBS zones.

ARQ and HARQ are not applicable to multicast connections as there is no feedback from the SS at layer 1 or layer 2. However MBS may be used with time-diversity enabled allowing a HARQ like behavior, where some HARQ parameters are used for MBS bursts to allow proper sequencing and time diversity combining when MBS bursts are retransmitted, without requiring any layer 1 or layer 2 acknowledgements from the SS.

Logical Channel IDs, which pairs with Multicast CID in the Extended MBS DATA IE, is allocated to each MBS Contents ID value in the order that it is included in the MBS Contents IDs TLV(11.13.37). As a result, an SS can receive multiple MBS messages for an MBS connection with different MBS contents distinguished by Logical Channel ID belonging to a Multicast CID. The BS shall allocate MBS SDUs in the order defined in the Extended MBS DATA IE.

If a DL multicast connection is to be encrypted, each SS participating in the connection shall have an additional security association (SA) allowing that connection to be encrypted using keys that are independent of those used for other encrypted transmissions between the SS and the BS.

Multicast and broadcast service flows may be encrypted at the application layer or MAC or both. Upper layer encryption may be employed to prevent non-authorized access to multicast and broadcast content. MBS may provide access control against theft of service by enforcing data encryption based on advanced encryption standard with counter mode encryption (AES-CTR) defined in NIST Special Publication 800-38A and FIPS 197. Details of MBS security are defined in 7.8.3.

For all BSs that belong to the same MBS Zone, the following coordination shall be assured:

- Mapping of SDUs into the MBS Bursts should be identical, and the same SDU's shall be transmitted in the same frame in all BS in the same MBS Zone;
- Packets of the MBS content shall be classified and mapped to SDUs identically at each BS within the MBS Zone;
- SDU fragment sequence number and fragmentation size across frame transmissions must be identical.

Coordination in the MBS Zone assures that the SS may continue to receive MBS transmissions from any BS that is part of the MBS Zone, regardless of the SS operating mode—Normal Operation, Idle Mode—without need for the SS to register to the BS from which it receives the transmission.

In addition to coordination, MBS transmissions may optionally be synchronized across all BS's within an MBS Zone. This option enables an SS to receive the multicast or broadcast transmission from multiple BS using macro-diversity, and thereby improve the reliability of reception. When Macro-diversity is enabled additional parameter may also be required to be the same across BS's if macro-diversity is used, see section 6.3.23.2

A BS may provide the SS with MBS content locally within its coverage and independently of other BSs. The single BS provision of MBS is therefore a configuration where an MBS Zone is configured to consist of one BS only. This configuration may be provided as one of the possible cases of multi-BS MBS. In this case, the BS may use any multicast CID value for providing the MBS service, independently of other BSs. In single-BS-MBS access, the SS receives the MBS data from its serving BS, and the SS should not expect the service flow for this MBS connection to continue should the SS leave the serving BS.

#### **6.3.23.1 Establishment and maintenance of MBSs**

Establishment of MBSs with respect to certain service flow is always performed when SS is in Normal Operation with a serving BS. MBSs are associated with multicast and broadcast service flows. Multicast and broadcast service flows are not dedicated to the specific SS and are maintained even though the SS is either in awake/sleep mode or in the idle mode. When an SS is registered at a BS for receiving MBS, multicast and broadcast service flows shall be instantiated as multicast connections. Data of multicast and broadcast service flows may be transmitted from BS and received at SS also regardless of what mode the SS is currently in. The BS may establish a DL MBS by creating a multicast and broadcast service flows when the service commences. Mapping of multicast and broadcast SFIDs to CIDs shall be known to all BSs belonging to the same MBS zone. The method of making all BS in the same MBS Zone aware of MBS flows and associated MBS Service Flows—including multicast CID assignment, QoS parameter set, and Classification Rule(s)—is outside the scope of the standard. As the classification and transmission of MBS flows may be supported on a BS in an MBS Zone regardless of the presence or absence of any SS in Normal Operation receiving the service, the BS may retain MBS service flow management encodings sufficient to do classification and scheduling of received MBS flows, even when no SS participating in the service is active on the BS.

When the SS registers at the BS for receiving multicast and broadcast services, the BS or SS may initiate the DSA procedure with respect to multicast and broadcast connections. Such knowledge may be used to initiate bi-directional upper layers communication between the SS and the network for the purpose of configuration of multicast/broadcast service. After successful configuration, the SS shall reuse the same configuration when it moves to another BS without re-configuration.

During communication to the BS the SS may learn the MBS\_Zone ID. The SS may continue to receive MBS transmissions from any BS that is part of the MBS Zone, regardless of the SS operating mode—Normal Operation, Idle Mode—without need for update to any service flow management encoding for the MBS flow.

Should the SS transit to a new MBS Zone while in Normal Operation, and provided that SS MBS service flow management encodings have not otherwise been updated using the method provided in section 6.3.23.1.1, as part of the handover the BS may include CID\_Update in REG-RSP encoding TLV in the RNG-RSP to provide updated service flow management encodings for any affected MBS flow.

When an SS in Idle mode migrates to a BS advertising another MBS\_Zone, the SS is expected to have the MBS service flow management encodings updated at that BS, to acquire update on one or more of multicast CID Target SAID parameter, Packet Classification Rule parameter(s), MBS Zone Identifier Assignment parameter, and MBS contents IDs, to provide for further reception of MBS content. If the SS has not received such information from the serving MBS\_Zone as described in section 6.3.23.1.1, the SS may conduct location update to acquire updated MBS service flow management encodings, or may conduct re-entry from Idle mode. The BS may include CID\_Update in REG-RSP encoding TLV in the RNG-RSP to provide updated service flow management encodings for any affected MBS flow.

During a Dynamic Service Addition procedure, the BS may include the MBS contents IDs TLV (11.13.37) in the DSA-REQ or DSA-RSP message to establish an MBS service flow for multiple MBS contents. . The BS may include MBS Contents Identifier TLV in DSA-REQ/RSP to establish an MBS connection with multiple MBS contents.

The SS shall not include the MBS\_Zone ID or MBS contents IDs in a DSA-REQ message.

#### **6.3.23.1.1 Inter-MBS Zone transition**

To allow seamless transition from one MBS Zone to another without any interruption of MBS data service and operation, the MS shall update MBS service flow management encodings including multicast CID, Target SAID parameter, Packet Classification Rule parameter(s), MBS Zone Identifier Assignment parameter, and MBS contents IDs.

Upon detection of MBS Zone change SS shall not request the new MCIDs from target MBS Zone and shall use stored MBS configuration information when available. The method of acquiring the stored update MBS Zone information is outside the scope of this standard.

If the SS has no MCID information regarding the new MBS Zone, then the SS is required to acquire MCID context through the other procedures, e.g., location-update, handover, or network-entry.

If the SS has an indication that the MCID has no continuity in the target MBS zone then the SS shall delete the MCID and MBS Zone Identifier Assignment related to the MCID, while the corresponding MBS service flows become provisioned but not active.

If the SS holds provisioned MBS service-flows and it moves to another MBS Zone then the SS shall perform MCID update procedure only for the provisioned service-flows.

#### **6.3.23.2 Performance enhancement with macro diversity**

Multiple BS's participating in the same multi-BS-MBS service MAY be time and frequency synchronized in the transmissions of common MBS data to allow macro diversity gain at the SS. When macro-diversity is enabled the MBS bursts positions and dimensions as well as PHY parameters shall be the same across all BS's within the same MBS Zone. In addition to the coordination parameters identified in 6.3.23.1, macro-diversity synchronization requires that all BS's within the same MBS Zone shall use the same:

- DUIC parameters associated with each MBS Burst including FEC Type, Modulation Type, and Repetition Coding;
- Mapping of SDUs to PDU (order of the SDUs and fragments) including Sub Headers;
- Mapping of PDUs to bursts;
- Order of bursts in the zone/region;
- MAP construction

The way that multiple BSs accomplish the synchronized transmission (which implies performing functions like classification, fragmentation, scheduling at a centralized point called the MBS Server) is outside the scope of the standard.

**6.3.23.3 Power saving operation** To facilitate power efficient reception of MBS data, an MBS MAP IE may be placed in the DL-MAP to point to the location of a dedicated MBS region allocation in the DL subframe. The purpose of this IE is to do the initial direction of the SS to the MBS allocation, and to redirect any SS that has lost synchronization with MBS allocations back to the next MBS allocation.

#### 6.3.23.4 Multicast and broadcast zone (MBS\_Zone)

Different CIDs or different SAs may be used in different service areas for the same multicast and broadcast service flow. A multicast and broadcast zone identifier (MBS\_ZONE\_ID) is used to indicate a service area through which a CID and SA for a broadcast and multicast service flow are valid. A BS that supports Multi-BS Access MBS shall include the MBS zone identifier(s) as a MBS zone identifier list in the DCD message (see Table 543). The MBS zone identifier shall not be '0'.

When the MBS zone identifier list appears in DCD settings TLV in MOB\_NBR-ADV message with only one value of '0', then the neighbor BS is not affiliated with any MBS zone.

In case BS sends DSA for establishment of connection for MBS, MBS\_ZONE shall be encoded in the DSA message (see 11.13.29). If an SS in Idle mode moves into BSs in the same MBS zone, the SS does not have to re-enter the network to re-establish a connection or a connection defined by MBS Contents Identifier to monitor the multicast and broadcast service flow. However, if an SS moves into a different MBS zone, the SS may need to update service flow management encodings for the multicast and broadcast service flow. One BS may have multiple MBS zone IDs for different MBS services.

#### 8.4.5.3.12 MBS MAP IE

*[Modify 8.4.5.3.12 after the table as:]*

**Macro diversity enhanced** Indicates [if macro-diversity is used for](#) access to MBS. If this value is 1, the type of access is Multi-BS Access [with Macro-Diversity](#). If this value is 0, [it indicates that Macro-diversity is not used](#).

**Next MBS\_MAP\_IE Frame Offset** The Next MBS\_MAP\_IE Frame Offset value is lower 8 bits of the frame number in which the BS shall transmit the next MBS MAP IE frame.

~~For the case of multi-BS MBS, an~~ [The](#) MBS MAP message shall be located at the first subchannel and first OFDMA symbol of the [MBS region DL-permutation-zone reserved for MBS](#) that is specified by the MBS MAP IE when 'Macro diversity enhanced' is set to 1. This [MBS Region DL-permutation-zone for MBS](#) shall be located in the same frame as the MBS MAP IE that specifies it. The location of this [MBS Region DL-permutation-zone for MBS](#) within the frame is specified by 'OFDMA Symbol Offset' in MBS MAP IE ~~when 'Macro diversity enhanced' is set to 1.~~

*[Modify 11.13.23 as:]*

#### 11.13.23 MBS service TLV

This TLV indicates whether the MBS service is being requested [or provided](#) for the connection that is being set up. A value of 1 indicates [that an MBS service limited to the serving BS is being](#) ~~Single-BS MBS is~~ requested and a value of 2 indicates ~~m~~Multi-BS-MBS is [being](#) requested. If SS or BS wants [to](#) initiate MBS service, DSA-REQ with MBS service [TLV](#) shall be used. The DSA-RSP message shall contain the acceptance or rejection of request and if there is no available MBS, MBS service value [shall](#)~~may~~ be set to 0. ~~ARQ shall not be enabled for this connection.~~

Type	Length	Value	Scope
[145/146].4	1	0: No available MBS 1: <del>Single-BS-MBS</del> <a href="#">MBS in Serving BS Only</a> 2: <del>Multi-BS-MBS</del> <a href="#">MBS in a multi-BS Zone</a>	DSA-REQ DSA-RSP DSA-ACK